

DT
125

Its maintenance simplicity does the difference because no ground conditions can terrify the 2-stroke engine and the monocross suspension of the DT125. Easy to repair, and cheap to maintain, this is one of the references of the governments, NGOs, and companies.



Colors
available



MOTOR

Engine type	Single cylinder, 2-stroke
Displacement (cc)	124
Cooling system	Air-cooled
Bore x Stroke (mm)	56 x 50,7
Compression ratio	6.7:1
Maximum torque (N.m / rpm)	15,2 N.m à 6 500 tr/min
Starter system	Kick Starter
Lubrication system	N/C
Ignition system	CDI (Electronic)
Fuel delivery	Carburettor



CHASSIS

Frame	Double cradle
Front suspension system	Telescopic fork
Rear suspension system	Swingarm
Front brake	Single hydraulic disc
Rear brake	Drum
Wheels	Spoke wheels
Front tyre	2,75-21 4
Rear tyre	4,10-18 4



DIMENSIONS

Overall dim - L x w x h (mm)	2110*865*1165
Wheelbase (mm)	1415
Seat height (mm)	885
Min ground clearance (mm)	260



TRANSMISSION

Transmission system	6-speed Manual
---------------------	----------------



WEIGHT/CAPACITIES

Dry weight (kg)	98
Fuel tank capacity (L)	9,50



EQUIPMENT



Luggage
rack



Kick
starter



Spoke
wheels

THE
rules

1 Always wear a helmet, eye protection and protective proper clothing.

2 Yamaha encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

For more information, please contact your dealer Yamaha.

cfao
MOBILITY